

LEXCOR

LEXPLAST

Plastic Roof Cement

DESCRIPTION & USE

LEXPLAST Roof plastic cement is a multipurpose professional product made of asphaltic bitumen. It is asbestos free. LEXPLAST is easy to use and create a strong and resistant layer protecting from weathering.

LEXPLAST is used for cement filling and sealing joints in concrete, masonry, wood or metal building construction, or for sealing flashings, skylights, parapet walls and for repairing leaks and cracks of all types. It is particularly suited for trowel applications.

TECHNICAL DATA

LEXPLAST		
	Summer Grade	Winter Grade
Formats	13.6 kg 20 kg	13.6 kg 20 kg
Colour	black	black
Solids	70% - 80%	65% - 75%
Density	1.15 g/L (9.6 lbs/gal)	1.05 g/L (8.8 lbs/gal)
Application Temperature¹	± 10°C to 25°C (± 50°F to 77°F)	under 10°C (under 50°F)
Drying Time²	48 hours	48 hours
Shelf Life-Time	12 months unopened	12 months unopened

¹ For best results under any temperature, temper the product before application.

² Drying time depends on application method, weather and surfaces porosity.

COVERAGE

- 13.6 kg for ± 4.35 m² (13.8 ft²)
- 20 kg for ± 6.41 m² (69 ft²)

Coverage depends on the surfaces porosity and the weather.



Complies with CAN/ONGC 37-5M-89.

APPLICATION INSTRUCTIONS

Surface should be firm and free from moisture, grease, loose particles, cracks, frost, snow, ice, oil and other foreign matter.

Apply by knife, trowel or glove. Single coatings should not be more than 3 mm (1/8 in.) thick.

RESTRICTIONS

- Harmful and flammable liquid and vapors.
- Keep away from heat sources, sparks and flames.
- Use only with adequate ventilation.
- Do not breathe vapors.
- Wear safety glasses and appropriate gloves.
- Use mineral spirits for cleanup.

Visit our video channels: <https://vimeo.com/channels/lexcoren>

COMMERCIAL BUILDING PRODUCTS

Ontario & Western Canada
1.800.268.2889



Quebec & Eastern Canada
1.800.363.2307

lexcor.net