

FLASH-TITE MASTIC CUPS

DESCRIPTION & USE

LEXCOR has a complete range of FLASH-TITE MASTIC CUPS to accommodate virtually any roof projection such as:

- Wire anchors
- Antennas
- Sign supports
- Equipment pods
- Electrical conduits
- Column stubs

Available in aluminum, sizes range from 50 mm (2") to 300 mm (12") in diameter and either 125 mm (5") or 225 mm (9") in height for conventional or inverted roofs respectively. LEXCOR can also provide a flexible polyurethane foam to insulate and prevent condensation at the bottom of the cup, plus a wide range of mastics and sealants to "top off" and seal the top of the cup.

To fill the Mastic Cup:

1. Select the foam width, 100mm (4") for conventional roofs or 200 mm (8") for inverted roofs, and foam thickness, 25 mm (1") or 50 mm (2"). Cut to desired length.
2. Compress foam and insert into MASTIC CUP so that it fills the entire void between the roof projection and the inside wall of the MASTIC CUP. Make sure the foam is at least 19 mm (¾") below the top of the MASTIC CUP.
3. Fill the top of the MASTIC CUP with specified mastic sealant, being sure to "cant" the mastic or sealant to facilitate water run-off.

Note: Most asphalt mastics contain 50% to 70% solids, therefore, 30-50% shrinkage can occur. This necessitates re-filling the mastic cup 4-6 months after completion. Most sealants, on the other hand, are 80-100% solids and very little shrinkage should occur.

FEATURES & BENEFITS

Seamless Construction - MASTIC CUPS contain no joints that might rupture under stress.

Fully Compatible - MASTIC CUPS can be used with modified bitumen, built-up or single ply roofing systems.

Optional Insulation - MASTIC CUPS are available with optional insulation to avoid condensation in colder climates.



TECHNICAL DATA

| Dimensions | | | |
|------------|-------------|--------------|-------------|
| Model No. | Height | Diameter | Flange |
| LEXMC 5-2 | 125 mm (5") | 50 mm (2") | 100 mm (4") |
| LEXMC 5-4 | 125 mm (5") | 100 mm (4") | 100 mm (4") |
| LEXMC 5-6 | 125 mm (5") | 150 mm (6") | 100 mm (4") |
| LEXMC 5-8 | 125 mm (5") | 200 mm (8") | 100 mm (4") |
| LEXMC 5-10 | 125 mm (5") | 250 mm (10") | 100 mm (4") |
| LEXMC 5-12 | 125 mm (5") | 300 mm (12") | 100 mm (4") |
| LEXMC 9-2 | 225 mm (9") | 50 mm (2") | 100 mm (4") |
| LEXMC 9-4 | 225 mm (9") | 100 mm (4") | 100 mm (4") |
| LEXMC 9-6 | 225 mm (9") | 150 mm (6") | 100 mm (4") |
| LEXMC 9-8 | 225 mm (9") | 200 mm (8") | 100 mm (4") |
| LEXMC 9-10 | 225 mm (9") | 250 mm (10") | 100 mm (4") |
| LEXMC 9-12 | 225 mm (9") | 300 mm (12") | 100 mm (4") |

SPECIFICATION

FLASH-TITE MASTIC CUPS (and protection cap), where indicated on the drawings, shall be LEXCOR MASTIC CUPS installed in strict accordance with the manufacture details.

WARRANTY

This product's lifetime warranty ensures it remains free from manufacturing defects and will perform its intended function throughout the entire lifespan of the roofing system.



COMMERCIAL BUILDING PRODUCTS

Ontario & Western Canada 1.800.268.2889 / Quebec & Atlantic 1.800.363.2307

Distr. By/Par Lexsuco 2010 Corporation, 3275 Orlando Drive, Mississauga, ON, L4V 1C5

19082024