FIBRELEX 1" Asphalt Coated High Strength **Roof Insulation**

DESCRIPTION & USE

- Composed of interlocking fibres impregnated with a water-repellent petroleum wax emulsion that imparts a high resistance to moisture absorption
- Excellent substrate for the roofing membrane
- Ideal surface for the application of hot asphalt

Fibrelex Asphalt Coated High Strength Roof Insulations can be used as follows:

As a roof insulator

TECHNICAL DATA

- As a cap sheet over other insulations
- As a separation board between old and new roofs
- As an underlay on steel decks applications
- As raw material in the making of slope insulation and/or cant strips

1" FIBRELEX - PHYSICAL PROPERTIES Requirement Results Characteristics Test Method Thermal Resistance, RSI - 0.455 ASTM Pass 25.4 mm C518 (R - 2.58) Transverse Load at Rupture ASTM 60 N Pass min. (either direction) C209 (13.4 lbF) Compressive Strength @ ASTM 100 kPa Pass 10% deformation, Min. C165-A (14.5 psi) Tensile Parallel to Surface, ASTM 350 kPa Pass (machine direction) Min. C209 (50.8 psi) Tensile Perpendicular to 24 kPa Pass ASTM Surface, Min. C209 (3.5 psi) Linear Moisture Expansion, ASTM 0.5% Pass D1037 max. Water Absorption, max. ASTM 10% Pass C209

1" FIBRELEX - SIZE & PACKAGING			
Item Number	Dimensions	Panels per bundle	Coverage per bundle
HSFB1X2X4OSC	610 mm x 1219 mm (24″ x 48″)	6	4.5 m² (48 ft²)
HSFB1X2X4TSC	610 mm x 1219 mm (24" x 48")	6	4.5 m² (48 ft²)

Note: Panels are available with shiplap, square or air channel edges.

Note: Fibrelex Asphalt Coated High Strength Roof Insulations must be stored above the deck or ground level and adequately protected from the elements with tarpaulins.

APPLICABLE STANDARDS

- CAN/ULC-S706-09 TYPE I & TYPE II, Class 1
- FM Approved

FEATURES & BENEFITS

- Very High Compressive Strength increases the rigidity and strength of the roof system
- Very Good Insulating Properties surpasses typical requirements and meets applicable standards

cornet

Visit our video channels: https://vimeo.com/channels/lexcoren

EXCOR

COMMERCIAL BUILDING PRODUCTS

Ontario & Western Canada 1.800.268.2889

Quebec & Eastern Canada 1.800.363.2307