## **UNIVERSAL**

# **GEOLEX NW90** NON-WOVEN POLYESTER GEOTEXTILE

# **DESCRIPTION & USE**

GEOLEX NW90 is a non-woven polyester geotextile. It can be used in roofing, building envelope and infrastructure applications.

Typically, GEOLEX NW90 provides the following functions:

## Separation

To separate 2 layers so the integrity of both layers is maintained or improved

#### Filtration

To allow the passage of fluids while preventing the passage of particles

## Reinforcement

To add tensile strength, as well as resist stresses or contain deformations in soil structures

### Protection

To prevent or reduce damage, such as cuts and punctures, to an adjacent surface or layer

### Drainage

To collect and transport fluids within its own thickness.

# **FEATURES & BENEFITS**

**Resistant to Biological Degradation -** not affected by microorganisms such as fungi and bacteria

**Chemical Resistant -** able to withstand exposure to natural bases or acids

Easy to Apply - requires no mixing

# PACKAGING

3.81 m x 100.00 m (12,5' x 328.08') roll

# **INSTALLATION**

In many applications, GEOLEX NW90 is simply unrolled and loose laid in position.

## **SPECIFICATION**

## Geotextile

- 1. Description: a non-woven polyester geotextile
- 2. Specified Product: Lexcor Geolex NW90 by Lexsuco Corporation



# **TECHNICAL DATA**

Index Properties	Test Method	Values
Ultimate Tensile Strength, MD	ASTM D4595	8.0 kN/m
Ultimate Tensile Strength, TD	ASTM D4595	8.0 kN/m
Elongation at Nominal Breaking Strength	ASTM D4595	50-100 %
Grab Tensile Strength	ASTM D4632	410 N
Tear Strength, MD	ASTM D4533	200 N
Tear Strength, TD	ASTM D4433	200 N
Punching CBR	ASTM D6241	1400 N
Pore Opening	ASTM D4751	70 µm max
Permittivity	ASTM D4491	0.61 s <sup>-1</sup> L/m²/s
Vertical Permeability Coefficient	ASTM D4491	0.12 cm/s
UV Resistance @500 Hours	ASTM D4355	80 %@500h
Weight	ASTM D5261	185 g/m²
Thickness	ASTM D5199	1.3 mm
Mass Deviation Rate per Unit Area	-	± 5 %
Width Deviation Rate	-	± 0.5 %
Thickness Deviation Rate	-	± 10 %

Colour

Geolex NW90 is available only in white.

# COMMERCIAL BUILDING PRODUCTS

Ontario & Western Canada 1.800.268.2889 Quebec & Atlantic Canada

13823