

SDS Revision Date: 02/01/2020

### 1. Identification

1.1. Product identifier

Product Identity502 MS Karna-FlexAlternate Names502 MS Karna-Flex

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended useSee Technical Data Sheet.Application MethodSee Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Karnak Corporation

330 Central Ave. Clark, NJ 07066 USA

**Emergency** 

CHEMTREC (USA) (800) 424-9300

**24 hour Emergency Telephone No.**OUTSIDE THE U.S AND CANADA 1-202-483-7616

Customer Service: Karnak Corporation 1-800-526-4236

### 2. Hazard(s) identification

#### 2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.

#### 2.2. Label elements

UFI#: R800-U0RP-S00A-1AQ1

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



H226 Flammable liquid and vapor.

[Prevention]:



**SDS Revision Date:** 

02/01/2020

- P210 Keep away from heat / sparks / open flames / hot surfaces No smoking.
- P235 Keep cool.
- P240 Ground / bond container and receiving equipment.
- P241 Use explosion-proof electrical / ventilating / light / equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe mist / vapors / spray.
- P262 Do not get in eyes, on skin, or on clothing.
- P280 Wear protective gloves / eye protection / face protection.

### [Response]:

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P331 Do NOT induce vomiting.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

### [Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

### [Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.



SDS Revision Date: 02/01/2020

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Calcium carbonate CAS Number: 0001317-65-3	10 - 25	Not Classified	[1][2]
Solvent naphtha (petroleum), light aromatic CAS Number: 0064742-95-6	10 - 25	Asp. Tox. 1;H304	[1]
Styrene-Butylene Copolymer CAS Number: Proprietary	10 - 25	Not Classified	[1]
Hydrocarbons, C6-20, polymers, hydrogenated CAS Number: 0069430-35-9	10 - 25	Combustible Dust	[1]
Titanium dioxide CAS Number: 0013463-67-7	1.0 - 10	Not Classified	[1][2]
Amorphous fumed silica CAS Number: 0112945-52-5	1.0 - 10	Combustible Dust	[1]
Quaternary ammonium compounds, benzylbis(hydrogenated tallow alkyl)methyl, bis(hydrogenated tallow alkyl)dimethylammoniu CAS Number: 0121888-67-3	1.0 - 10	Not Classified	[1]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. First aid measures

### 4.1. Description of first aid measures

**General** In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

**Inhalation** If respiratory discomfort occurs, remove to fresh air. If discomfort continues, administer

oxygen and get medical attention.

**Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and

seek medical attention.

**Skin** If this product comes in contact with skin, remove material with mineral oil, then wash with

soap and plenty of water.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

<sup>[1]</sup> Substance classified with a health or environmental hazard.

<sup>[2]</sup> Substance with a workplace exposure limit.

<sup>[3]</sup> PBT-substance or vPvB-substance.

<sup>\*</sup>The full texts of the phrases are shown in Section 16.



SDS Revision Date:

02/01/2020

#### 4.2. Most important symptoms and effects, both acute and delayed

### Overview

Fumes from product can be unpleasant, may cause nausea, headache and irritating to eyes, skin, and respiratory tract. **POTENTIAL HEALTH EFFECTS** 

**Eye Contact:** May cause tearing, stinging, redness, irritation, and burns. **Inhalation:** Irritating to respiratory tract. Prolonged or repeated breathing of very high

vapor concentrations cause euphoria, excitation, and dizziness, headaches, nausea, and vomiting, abdominal pain, fatigue, muscular weakness. Aspiration into the lungs can cause CNS (central nervous system) and subsequent aspiration into the lungs can cause pulmonary edema and chemical pneumonia depression. Chronic overexposure in high concentrations may produce CNS depression.

Ingestion: Irritation of the mouth, esophagus, and stomach can develop following ingestion. Symptoms include burning of the mouth, sore throat, vomiting, nausea, dizziness, loss of consciousness. Due to its light viscosity, there is danger of aspiration into the lungs during vomiting. Aspiration can result in severe lung damage or death.

Skin Contact: Prolonged or repeated skin contact may cause moderate to severe irritation including itching and redness of the skin, defatting, and/or dermatitis. This product can also be absorbed through the skin and produce CNS symptoms. Single prolonged exposure is not likely to result in the product being absorbed through the skin in harmful amounts.

Signs And Symptoms Of Exposure: Eye irritation, respiratory irritation, drying and cracking of skin, dizziness, fatigue, headache, unconsciousness or asphyxiation. Chronic effects of ingestion and subsequent aspiration into the lungs can cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Repeated breathing of vapors can cause effects to liver and kidneys.

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

**SDS Revision Date:** 

02/01/2020



### 5. Fire-fighting measures

### 5.1. Extinguishing media

Carbon dioxide (CO2), foam, or dry chemical. Water may be used to Cool containers exposed to heat.

### 5.2. Special hazards arising from the substance or mixture

When heated above flash point, material will release flammable vapors which can burn or be explosive in confined spaces if ignited. Do not mix with strong oxidants such as chlorine or concentrated oxygen.

Hazardous decomposition: Hazardous decomposition products include carbon dioxide (CO2), carbon monoxide (CO) Nitrogen oxides, smokes and fumes.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe mist / vapors / spray.

Do not get in eyes, on skin, or on clothing.

### 5.3. Advice for fire-fighters

When heated above flash point, material will release flammable vapors which can burn or be explosive in confined spaces if ignited. Do not mix with strong oxidants such as liquid chlorine or concentrated oxygen.

Minimize breathing vapors, gases or fumes of decomposition products. Do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

ERG Guide No. ----

### 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

When heated above flash point, material will release flammable vapors which can burn or be explosive in confined spaces if ignited. Do not mix with strong oxidants such as chlorine or concentrated oxygen.

### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.



**SDS Revision Date:** 

02/01/2020

### 6.3. Methods and material for containment and cleaning up

When heated above flash point, material will release flammable vapors which can burn or be explosive in confined spaces if ignited. Do not mix with strong oxidants such as chlorine or concentrated oxygen.

Dike or contain spill with earth, floor dry, sand etc. Ventilate the area. Absorb spill with suitable absorbent material and place in a closed container.

Keep product out of sewers and waterways by diking or impounding. Advise authorities if product has entered or may enter sewers or waterways. Assure conformity with applicable governmental regulations.

Eliminate ignition sources. Soak up with noncombustible absorbent material. Remove absorbent material for proper disposal.

### 7. Handling and storage

#### 7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

### 7.2. Conditions for safe storage, including any incompatibilities

Vapors are heavier than air and may travel along the ground or be moved by ventilation to locations distant from the point of material handling. To prevent from entering buildings or confined areas, close all air intake sources near the material handling or the work area.

Avoid prolonged or repeated inhalation of vapors or spray mists. Avoid prolonged or repeated skin contact. Adhere to good hygienic practices. Use with adequate ventilation. Store in a cool, dry place, out of direct sunlight and away from heat, sparks, and flame.

Health studies have shown that many petroleum hydrocarbons pose potential human health risks which may Vary from person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

Incompatible materials: May react with strong oxidizing materials.

**Other Precautions:** All labeled precautions must be observed when handling, storing and transporting empty containers due to product residues. Do not reuse containers. Empty containers may contain material residues which can ignite with explosive force. Cutting or welding of empty containers can cause fire, explosion, or release fumes from residues. Keep containers closed and drum bungs in place. Dispose of in a licensed facility.

See section 2 for further details. - [Storage]:

### 7.3. Specific end use(s)

Health studies have shown that many petroleum hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.



02/01/2020



### 8. Exposure controls and personal protection

### 8.1. Control parameters

### **Exposure**

CAS No.	Ingredient	Source	Value
0001317-65-3	Calcium carbonate	OSHA	TWA 15 mg/m3 (total) TWA 5 mg/m3 (resp)
		ACGIH	TWA: 10 mg/m3 Ceiling: 20 mg/m3
		NIOSH	TWA 10 mg/m3 (total) TWA 5 mg/m3 (resp)
		Supplier	No Established Limit
0013463-67-7	Titanium dioxide	OSHA	TWA 15 mg/m3
		ACGIH	TWA: 10 mg/m32B, Revised 2006,
		NIOSH	Footnote ca
		Supplier	No Established Limit
0064742-95-6	Solvent naphtha (petroleum), light aromatic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
	Hydrocarbons, C6-20, polymers, hydrogenated	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0112945-52-5 Amorphous fumed silica	OSHA	No Established Limit	
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0121888-67-3	Quaternary ammonium compounds, benzylbis(hydrogenated tallow alkyl)methyl, bis(hydrogenated tallow alkyl)dimethylammoniu	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit



SDS Revision Date: 02/01/2020

The exposure limits for nuisance dust are: OSHA PEL: 15 mg/m3 (50 mppcf\*) TWA, ACGIH 10 mg/m3.

### Carcinogen Data

CAS No.	Ingredient	Source	Value			
0001317-65-3	Calcium carbonate	OSHA	Select Carcinogen: No			
		NTP	Known: No; Suspected: No			
			Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;			
0013463-67-7	0013463-67-7 Titanium dioxide		Select Carcinogen: No			
		NTP	Known: No; Suspected: No			
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;			
0064742-95-6	Solvent naphtha (petroleum), light aromatic	OSHA	Select Carcinogen: No			
		NTP	Known: No; Suspected: No			
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;			
	Hydrocarbons, C6-20, polymers, hydrogenated	OSHA	Select Carcinogen: No			
		NTP	Known: No; Suspected: No			
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;			
0112945-52-5	0112945-52-5 Amorphous fumed silica		Select Carcinogen: No			
		NTP	Known: No; Suspected: No			
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;			
0121888-67-3	Quaternary ammonium compounds, benzylbis(hydrogenated tallow alkyl)methyl, bis(hydrogenated tallow alkyl)dimethylammoniu	OSHA	Select Carcinogen: No			
		NTP	Known: No; Suspected: No			
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;			

### 8.2. Exposure controls

**Respiratory** Use supplied-air respirator in confined areas or with vapors in high concentrations.

**Eyes** Safety glasses or face shield for liquid material.

**Skin** Long sleeves and impervious clothing to protect against splashing. Solvent impervious

gloves should be worn.

**Engineering Controls** Mechanical/Local Exhaust may be necessary in enclosed areas.

Other Work Practices Long sleeves and impervious clothing to protect against splashing.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or

using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:



SDS Revision Date: 02/01/2020

### 9. Physical and chemical properties

Appearance White to colored Liquid

Odor Mild Petroleum
Odor threshold Not determined

**pH** Not Measured

Melting point / freezing point NA
Initial boiling point and boiling range 300-350F

Flash Point (PMCC): 107F min.

Evaporation rate (Ether = 1) (Butyl Acetate=1)@77F: 0.2

Flammability (solid, gas) Not Applicable

Upper/lower flammability or explosive limits Lower Explosive Limit: Not Measured

Upper Explosive Limit: Not Measured

Vapor pressure (Pa) 3

Vapor Density (Air=1): > 4

Specific Gravity (H2O=1): 1.05 - 1.15
Solubility in Water Insoluble

Partition coefficient n-octanol/water (Log Kow)

Auto-ignition temperature

Not Measured

Not Measured

Decomposition temperature

Not Measured

Viscosity (cSt)

Not Measured

9.2. Other information

No other relevant information.

### 10. Stability and reactivity

#### 10.1. Reactivity

Hazardous Polymerization will not occur.

### 10.2. Chemical stability

Stable under normal circumstances.

### 10.3. Possibility of hazardous reactions

No data available.

#### 10.4. Conditions to avoid

Keep away from heat, spark, open flames

#### 10.5. Incompatible materials

May react with strong oxidizing materials.

### 10.6. Hazardous decomposition products



**SDS Revision Date:** 

02/01/2020

Hazardous decomposition products include carbon dioxide (CO2), carbon monoxide (CO) Nitrogen oxides, smokes and fumes.

### 11. Toxicological information

### **Acute toxicity**

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Based upon animal testing, the C9 aromatic hydrocarbon components (trimethylbenzenes and ethylmethylbenzenes) are presumed to cause fetal toxicity and/or decreased fetal and newborn weights if overexposure occurs during the early gestation period.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Calcium carbonate - (1317-65-3)	No data available	No data available	No data available	No data available	No data available
Solvent naphtha (petroleum), light aromatic - (64742-95-6)	6,800.00, Rat - Category: NA	3,400.00, Rabbit - Category: 5	No data available	No data available	No data available
Hydrocarbons, C6-20, polymers, hydrogenated - (69430-35-9)	No data available	No data available	No data available	No data available	No data available
Titanium dioxide - (13463-67-7)	10,000.00, Rat - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA	No data available
Amorphous fumed silica - (112945-52-5)	3,160.00, Rat - Category: 5	No data available	No data available	No data available	No data available
Quaternary ammonium compounds, benzylbis(hydrogenated tallow alkyl)methyl, bis(hydrogenated tallow alkyl)dimethylammoniu - (121888-67-3)	No data available	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).



**SDS Revision Date:** 

02/01/2020

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable

### 12. Ecological information

### 12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and GHS and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details

### **Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l	
Calcium carbonate - (1317-65-3)	Not Available	Not Available	Not Available	
Solvent naphtha (petroleum), light aromatic - (64742-95-6)	9.22, Oncorhynchus mykiss	6.14, Daphnia magna	19.00 (72 hr), Selenastrum capricornutum	
Hydrocarbons, C6-20, polymers, hydrogenated - (69430-35-9)	Not Available	Not Available	Not Available	
Titanium dioxide - (13463-67-7)	Not Available	Not Available	Not Available	
Amorphous fumed silica - (112945-52-5)	Not Available	Not Available	Not Available	
Quaternary ammonium compounds, benzylbis(hydrogenated tallow alkyl)methyl, bis(hydrogenated tallow alkyl)dimethylammoniu - (121888-67-3)	Not Available	Not Available	Not Available	



SDS Revision Date: 02/01/2020

### 12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

### 13. Disposal considerations

#### 13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

### 14. Transport information

**DOT (Domestic** Ground IMO / IMDG (Ocean ICAO/IATA Transportation) **Transportation**) Exemption: 173.150(f)(2): FP >= 38 °C (100 °F), no other hazard class, reclassed as combustible 14.1. UN number UN1263 UN1263 14.2. UN proper shipping liquid, non-bulk is not regulated Paint Related Material Paint Related Material 14.3. Transport hazard **IMDG**: 3 Air Class: 3 class(es) 14.4. Packing group Ш Ш 14.5. Environmental hazards EmS No. F-E, S-E **IMDG** Marine Pollutant: No ERG Guide 128 14.6. Special precautions for user IMDG: Marine Pollutant: No No further information ERG Guide 128



**SDS Revision Date:** 

02/01/2020

### 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA

Inventory.

WHMIS Classification

B3

**US EPA Tier II Hazards** 

Fire: Yes

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): No Delayed (Chronic): No

#### EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### **EPCRA 302 Extremely Hazardous:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### **EPCRA 313 Toxic Chemicals:**

Ethyl Benzene

#### California Proposition 65 (>0.0%):

⚠ WARNING: This product can expose you to chemicals including titanium dioxide, which is known to the State of California to cause cancer and/or reproductive hazards. For more information, go to www.P65Warnings.ca.gov.

### **New Jersey RTK Substances (>1%):**

Calcium carbonate

Titanium dioxide

### Pennsylvania RTK Substances (>1%):

Calcium carbonate

Titanium dioxide

### 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein.



SDS Revision Date: 02/01/2020

We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

Disclaimer: This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The information has been completed to the best of our knowledge and is believed to be accurate and reliable as from the date indicated. However, no warranty is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy oneself as to the suitability and completeness of such information for his own particular use.

**End of Document**