

LEXCAN

HI-FLEX EPDM

Pipe Boots

DESCRIPTION & USE

Lexcan Hi-Flex EPDM Pipe Boots are economical flashings ideal for quick and easy flashing of pipes.

This product is used to securely seal pipes while offering supreme tear resistance and reinforcement. EPDM Pipe Boots come pre-applied with strong bonding seam tape and with stainless steel hose clamps. They are available to accommodate pipe sizes: 1" through 6".

Using Pipe Boots eliminates the workmanship error in field fabrication and makes flashing pipes a clean, consistent approach.

TECHNICAL DATA

Physical Properties	
Material:	EPDM
Colour:	Black
Sizes:	Accommodates 1" - 6" pipes
Packaging:	10 per carton
Weight:	8 lbs per carton
Shelf Life:	1 year



INSTALLATION INSTRUCTIONS

1. Clean and prepare surface 15" in all directions from the penetration. Seal joint between EPDM membrane and pipe with Hi-Flex EPDM Lexflash or Lap Sealant.
2. Select proper size of the flashing and cut off above the index ring. When in doubt, cut smaller size.
3. Apply Hi-Flex EPDM PA-100 or SA-747 on base of EPDM membrane, place boot over projection and complete attachment of flashing to roofing.
4. Using the stainless steel hose clamp, place at the top of the boot and tighten to projection.
5. Seal top of roof with Hi-Flex EPDM Lap Sealant.

lexcan.com

LEXCAN SINGLE PLY ROOFING SYSTEMS

Ontario and Western Canada
1 877 792.8308



Quebec and Eastern Canada
1 800 363.2307