

LEXPRIME TG

TORCH GRADE ADHESIVE

DESCRIPTION & USE

LEXPRIME TG is a synthetic rubber-based adhesive specifically formulated for use with thermofused SBS modified bitumen membranes and hot-applied rubberized asphalt membranes. Quick setting, it is used to enhance the adhesion of torch and thermal applied roofing and waterproofing membranes when applied to concrete, drywall, masonry, metal surfaces and wood.

FEATURES & BENEFITS

Fast Drying – Dries quickly to allow for faster project completion.

Improved Adhesion - Ensures better adhesion, leading to more effective and long-lasting membranes.

Versatile Application - Suitable for use on a wide range of surfaces, making it a flexible solution for different projects.

Normal and Low Temperature Application - Can be used when ambient conditions and substrate temperature are above -10°C (14°F).

TECHNICAL DATA

Physical Property	Typical Value
Colour	Black
Density	0.85 g/ml
Dry Time	60 minutes (25°C, 60% RH)
Flash Point	<-18°C
Viscosity	25 - 70 cps
VOC	max 555 g/L; 65% wt.
Weight Solids	34 - 36%

PACKAGING

18.93 L (5 US Gallon) pail.

COVERAGE

3.9 - 7 m²/l (162 - 285 ft²/gal.)*

*Depends on porosity and texture of surface

STORAGE

Store indoors at room temperature, away from heat, ignition sources, open flames and direct sunlight.



SHELF LIFE

2 years, unopened

APPLICATION INSTRUCTIONS

Surface Preparation

Loose particles from surface must be removed. Surfaces must be dry, free from oils, grease and other contaminants.

Application

Stir well before use. Apply by brush, short nap roller or sprayer suitable for solvent based products. Product should only be applied in dry weather with the ambient and substrate temperature above -10°C (14°F). It must be allowed to dry thoroughly (approximately one hour) before attempting torch application of membrane. Actual drying time varies, depending on temperature and humidity.

CAUTIONS & LIMITATIONS

- Cold temperatures and high humidity will prolong dry times.
- Do not attempt to speed up dry times by heating adhesive with torch.
- Contains highly flammable solvents.
- Avoid sparking, use non-sparking tools.
- Avoid open flames.
- Ensure that the work area is properly ventilated.
- Wash tools and equipment with mineral spirits, toluene, or xylene.
- Prior to working with this product, consult product label and Safety Data Sheet (SDS) for necessary health and safety precautions.



COMMERCIAL BUILDING PRODUCTS

Ontario & Western Canada 1.800.268.2889 / Quebec & Atlantic 1.800.363.2307

Distr. By/Par Lexsuco 2010 Corporation, 3275 Orlando Drive, Mississauga, ON, L4V 1C5

All products manufactured and/or distributed by Lexsuco 2010 Corporation comply with the description and properties specified in the technical data sheet in effect at the date of manufacture and/or publication. Lexsuco 2010 Corporation may change the composition and/or usage of its products without prior notice.