

**Flexural Strength (CSA A231.1-14)**

PRODUCT	TEST DATE	WIDTH AND DEPTH AT FAILURE (mm)	STRENGTH (Mpa)
50mm Slabs	26/08/2020	330 and 49.6	6.85
45mm Slabs	08/05/2019	600 and 44.9	5.30
Solar Reflective Slabs	09/08/2017	600 and 43.9	5.50

**Compressive Strength (CSA A231.3-14, ASTM C140-09)**

PRODUCT	TEST DATE	CUBE SIZE (mm)	STRENGTH (Mpa)
Pavers	30/04/2019	78.6	66.8
50mm Slabs	26/08/2020	49.6	61.5
Retaining Walls	23/05/2019	10424	34.6

\*cross sectional area (mm<sup>2</sup>)

**Water Absorption (CAN/CSA-23.2-11C, A231.1-14, ASTM C140)**

PRODUCT	TEST DATE	SSD DENSITY (kg/m <sup>3</sup> )	ABSORPTION %
Pavers	30/04/2019	2205	3.9
50mm Slabs	26/08/2020	2313	2.3
45mm Slabs	13/05/2019	2264	3.6
Solar Reflective Slabs	09/08/2017	2304	3.8
Retaining Walls	23/05/2019	2196	3.7

**Freeze-Thaw Durability (CSA A231.1-14, ASTM C1262, ASTM C1645-06)**

PRODUCT	ACCUMULATIVE LOSS IN MASS (g/m <sup>2</sup> )	
	7 CYCLES	28 CYCLES
Pavers	3.7	21.4
50mm Slabs	2.2	29.4
45mm Slabs	12	90.9
Solar Reflective Slabs	3.6	9.9
Retaining Walls	20 CYCLES	
	0.08	0.9

**Permeable Paver Infiltration (ASTM C170, ASTM C1701 M-09)**

MODERNA	JOINT WIDTH (mm)	WATER WEIGHT (G)	M INFIL. RATE (mm/h)
Herringbone	5.7	18	64,212
Running Bond	11.5	18	78,825

1-800-BESTWAY (2378929)

bestwaystone.com

8821 Weston Road, Woodbridge, ON L4L 1A6

65 Anderson Blvd, Uxbridge, ON L9P 0C7

**Solar Reflectance Index**

Colour	SRI
Beige Mix	27
Buff Brown	21
Carrara	30
Driftwood*	29
Glacier Creek*	34
Golden Meadow	20
Grey*	35
Grey Mix	24
Kashmir Blend*	33
Red	27
Red Mix	22
Sahara Blend*	31
Salmon	26
Salmon Mix	21
Pearl	44
White (Basketweave)*	51
White (SR Paver)**	82

\*Meet LEED (29) non-roof

\*\*Meet LEED (80) rooftop